Lighting Solutions iLight User Interfaces



CLASSIC DALI

....

Classic DALI Control Plate Range

Key Features

- Integrated DALI communication interface
- Draws power from the DALI
 communications bus to simplify wiring
- Designed to compliment Wandsworth Series 3
- Range of metal face plate finishes available
- Scene buttons have integral LED feedback
- Blue LED indication on scene buttons
- Custom text options available on both buttons and face plates
- Suitable for standard single gang UK wall box
- CE & UKCA compliant to all relevant standards
- Designed and manufactured to ISO9001 standard

Overview

Classic DALI control plates are available in 4 button configurations. Individual scene buttons have backlight indicator lights and strong tactile feedback. There is also a custom button and face plate engraving service making DALI control plates fully flexible to meet the needs of your project.





Button Functions

Scene selection Scene raise/lower Channel raise/lower Toggle on/off Toggle raise/lower True off Open/close (for curtains or blinds) Raise/lower (for motorized screens) Task (start/stop a sequence)

Operating Conditions

Operating temperature: +2°C to +40°C

Relative humidity: +5 to 95% non condensing

Dimensions



Typical Schematic

LIGHT



Contact Us +44 (0)1923 495495

iLight

A brand of Signify Usk House, Llantarnam Park Cwmbran, NP44 3HD, UK

© 2022 Signify Holding All Rights Reserved

DALI CLASSIC Rev5 0622

Mechanical Data

Standard or custom text options available on both buttons and face plates Fits standard 35mm deep UK wallbox - not provided

Electrical Data

DALI Input Voltage: 9.5V DC - 22.5V DC supplied by the DALI communication bus

DALI Current: Draw 3.75 mA per device

Temperature Range: 0°C to +40°C

Humidity: 0% - 95% non condensing

DALI Wiring: Two-wire, non-polarized control

www.iLight.co.uk

Changes to the products, to the information contained in this document, and to prices are reserved; so are errors and omissions.

iLight is a registered trademark. All other trademarks are property of their respective owners.

enquiries@iLight.co.uk

