Lighting Solutions iLight User Interfaces





Ineo

Ineo Control Panel Range

Key Features

- Available in black & white finishes
- Standard or custom engraving on buttons
- IR enabled
- Configuration stored in Non Volatile EEPROM
- Firmware storage in reflashable FLASH
 memory over iCAN network
- Configurable start up mode
- CE & UKCA compliant to all relevant standards
- Designed and manufactured to ISO9001 standard







Overview

Ineo is a versatile range of specification grade control plates that set new standards in intuitive layout and operation. Users are quickly drawn to the large on/off button controls with associated up/down adjustments. Panels may be ordered with engraved buttons and a choice of 5 panel configurations. There is even a choice of button size and colour.

Ineo control plates can be ganged together to meet specific project needs. Individual buttons have backlight indicator lights and strong tactile feedback.

Ineo is the clean, elegant, and simple way to control lighting on your project.

www.iLight.co.uk

Button Functions

Scene selection Scene raise/lower Channel raise/lower

Toggle on/off

Toggle raise/lower

True off

Open/close (for curtains or blinds)

Raise/lower (for motorized screens)

Task (start/stop a sequence)

Mechanical Data

Buttons include scene, raise, lower, on, off functionality.

Choice of large or small button caps

Standard or custom engraving on buttons

Tap on/off feature to overide fade time

All plastic construction with a separate snap-on surround

Suitable for standard single gang UK wall box

Electrical Data

5 plate variants selectable via Source Controller

Each button individually configurable via iLight software

Variable fade times programmable from 0.1 seconds to 60 minutes per button

IR enabled

12V DC powered direct from iCANnetTM network

Tested to withstand 12kV electro-static discharge without damage or memory loss


Flash memory for future proof upgradeability

Environmental Data

Temperature Range: 0°C to +40°C Humidity: 0% - 95% non condensing

LIGHT

Dimensions



Button Configurations



6 Small buttons

Scene 2 Scene 3 3 Large buttons



4 Small buttons, On / Off, Raise & Lower






2 Large button, On / Off, Raise & Lower

2 Large buttons

Typical Schematic



Contact Us +44 (0)1923 495495

iLight A brand of Signify Usk House, Llantarnam Park Cwmbran, NP44 3HD, UK

© 2022 Signify Holding All Rights Reserved

INEO Rev13 1121

enquiries@iLight.co.uk

www.iLight.co.uk





Changes to the products, to the information contained in this document, and to prices are reserved; so are errors and omissions.

iLight is a registered trademark. All other trademarks are property of their respective owners.

